

# CJRXB | IP06-06LUTP-1100E-BLUNT

## Base Product



InstaPATCH® Cu GigaSPEED XL® U/UTP LSZH Preterminated Copper Cable, 360 1100 Evolve module to unterminated, 6 links

This product will be discontinued on: January 31, 2025

## Product Classification

<b>Regional Availability</b>	Asia   Australia/New Zealand   EMEA   Latin America   North America
<b>Portfolio</b>	CommScope®
<b>Product Type</b>	Copper trunk cable assembly
<b>Product Brand</b>	GigaSPEED XL®   InstaPATCH® Cu

## General Specifications

<b>ANSI/TIA Category</b>	6
<b>Cable Type</b>	U/UTP (unshielded)
<b>Conductor Type</b>	Solid
<b>Interface, Connector A</b>	360 1100 Evolve module
<b>Interface Feature, connector A</b>	Standard
<b>Interface, Connector B</b>	Unterminated
<b>Link Count</b>	6
<b>Wiring</b>	T568B

## Dimensions

<b>Cable Assembly Length Range (m)</b>	2 – 90
<b>Cable Assembly Length Range (ft)</b>	7 – 295

## Electrical Specifications

<b>dc Resistance, maximum</b>	0.3 ohm
<b>Safety Voltage Rating</b>	300 V

## Ordering Tree

# CJRXB | IP06-06LUTP-1100E-BLUNT

	1	2	3	4	5	6	7	8	9	10	11	12				
	C	A	A	A	C	-	1	1	H	A	B	B	F	O	S	O

  

Cable Type	Connector B	Orientation A	Orientation B	Link	Outlet Color	UOM	Length
<b>A</b> Cat 6A X10D – U/UTP (Plenum)	<b>A</b> Outlet* – Single Row Standard Density	<b>1</b> Trident Series Flat	<b>1</b> Trident Series Flat	<b>B</b> 6	<b>0</b> Not Applicable	<b>F</b> Foot	<b>12</b> XXX
<b>B</b> Cat 6A X10D – U/UTP (Riser)	<b>B</b> Outlet* – Dual Row Standard Density	<b>2</b> Right Paired Flat	<b>2</b> Right Paired Flat	<b>C</b> 8	<b>1</b> Black (BK)	<b>M</b> Meter	
<b>C</b> Cat 6A X10D – U/UTP (LSZH)	<b>C</b> Outlet* – Dual Row High Density	<b>3</b> Right Series Flat	<b>3</b> Right Series Flat	<b>D</b> 12	<b>2</b> Blue (BL)		
<b>D</b> Cat 6A X10D – F/UTP (Plenum)	<b>G</b> RJ45 Plug* – Single Row Standard Density	<b>4</b> Left Paired Flat	<b>4</b> Left Paired Flat	<b>E</b> 16	<b>3</b> White (WH)		
<b>E</b> Cat 6A X10D – F/UTP (Riser)	<b>H</b> RJ45 Plug* – Dual Row Standard Density	<b>5</b> Left Series Flat	<b>5</b> Left Series Flat	<b>F</b> 18			
<b>F</b> Cat 6A X10D – F/UTP (LSZH)	<b>J</b> RJ45 Plug* – Dual Row High Density	<b>6</b> Trident Paired Flat	<b>6</b> Trident Paired Flat	<b>G</b> 24			
<b>G</b> Cat 6 XL – U/UTP (Plenum)	<b>N</b> 1100 Module	<b>A</b> Trident Series Angled	<b>A</b> Trident Series Angled				
<b>H</b> Cat 6 XL – U/UTP (Riser)	<b>R</b> 360 1100 Evolve Module	<b>B</b> Right Paired Angled	<b>B</b> Right Paired Angled				
<b>J</b> Cat 6 XL – U/UTP (LSZH)	<b>S</b> OneLink 2x6	<b>C</b> Right Series Angled	<b>C</b> Right Series Angled				
<b>Q</b> Cat 6A X10D – S/FTP (LSZH)	<b>T</b> OneLink 2x4	<b>D</b> Left Paired Angled	<b>D</b> Left Paired Angled				
<b>R</b> Cat 6 – U/UTP Class B Rated (LSZH)		<b>E</b> Left Series Angled	<b>E</b> Left Series Angled				
<b>S</b> Cat 6A – U/UTP Class B Rated (LSZH)		<b>F</b> Trident Paired Angled	<b>F</b> Trident Paired Angled				
<b>Y</b> Cat 6A X10D SD – U/UTP (Riser)		<b>X</b> Not Applicable	<b>X</b> Not Applicable				

  

Connector A	Bundling	Jacket Color	Labeling
<b>A</b> Outlet* – Single Row Standard Density	<b>H</b> Hook-n-loop	<b>8</b> White (WH)	<b>8</b> A Generic Label
<b>B</b> Outlet* – Dual Row Standard Density	<b>S</b> Sleeving	<b>C</b> Slate (SL)	
<b>C</b> Outlet* – Dual Row High Density		<b>Z</b> Blue (BL)	
<b>G</b> RJ45 Plug* – Single Row Standard Density			
<b>H</b> RJ45 Plug* – Dual Row Standard Density			
<b>J</b> RJ45 Plug* – Dual Row High Density			
<b>N</b> 1100 Module			
<b>R</b> 360 1100 Evolve Module			
<b>S</b> OneLink 2x6			
<b>T</b> OneLink 2x4			
<b>X</b> Unterminated			

- Cords > 1m are authorized for use in channels and are an effective standalone method used to connect active devices
- Cords < 1m are also valid elements for use in a channel or as an equipment interconnect, but due to their limited length are not guaranteed to meet component compliance requirements that were developed to assess the quality of longer cords

## Environmental Specifications

<b>Operating Temperature</b>	-10 °C to +60 °C (+14 °F to +140 °F)
<b>Environmental Space</b>	Low Smoke Zero Halogen (LSZH)
<b>Flammability Rating</b>	UL 94 V-0

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

## Included Products

- |                                   |   |  |
|-----------------------------------|---|--|
| 3071E-4/23                        | – | GigaSPEED XL® 3071 ETL Verified Category 6 U/UTP Cable, low smoke zero halogen, 4 pair count |
| 760151167<br>360-IPR-1100-GS3-DM6 | – | SYSTIMAX 360™ GigaSPEED XL® 1100GS3 Evolve Category 6 U/UTP Distribution Module, 6 port      |

# 3071E-4/23

---



GigaSPEED XL® 3071 ETL Verified Category 6 U/UTP Cable, low smoke zero halogen, 4 pair count

## Product Classification

<b>Regional Availability</b>	Asia   Australia/New Zealand   EMEA   Latin America
<b>Portfolio</b>	SYSTIMAX®
<b>Product Type</b>	Twisted pair cable
<b>Product Brand</b>	GigaSPEED XL®

## General Specifications

<b>Product Number</b>	3071E
<b>ANSI/TIA Category</b>	6
<b>Cable Component Type</b>	Horizontal
<b>Cable Type</b>	U/UTP (unshielded)
<b>Conductor Type, singles</b>	Solid
<b>Conductors, quantity</b>	8
<b>Pairs, quantity</b>	4
<b>Separator Type</b>	Bisector
<b>Transmission Standards</b>	ANSI/TIA-568.2-D   CENELEC EN 50288-6-1   ISO/IEC 11801 Class E

## Dimensions

<b>Diameter Over Jacket, nominal</b>	5.918 mm   0.233 in
<b>Jacket Thickness</b>	0.508 mm   0.02 in
<b>Conductor Gauge, singles</b>	23 AWG

## Cross Section Drawing



## Electrical Specifications

<b>dc Resistance Unbalance, maximum</b>	5 %
<b>dc Resistance, maximum</b>	7.61 ohms/100 m   2.32 ohms/100 ft
<b>Mutual Capacitance at Frequency</b>	5.6 nF/100 m @ 1 kHz
<b>Nominal Velocity of Propagation (NVP)</b>	69 %
<b>Operating Frequency, maximum</b>	300 MHz
<b>Operating Voltage, maximum</b>	80 V
<b>Remote Powering</b>	Fully complies with the recommendations set forth by IEEE 802.3bt (Type 4) for the safe delivery of power over LAN cable when installed according to ISO/IEC 14763-2, CENELEC EN 50174-1, CENELEC EN 50174-2 or TIA TSB-184-A

## Material Specifications

<b>Conductor Material</b>	Bare copper
<b>Insulation Material</b>	Polyolefin
<b>Jacket Material</b>	Low Smoke Zero Halogen (LSZH)
<b>Separator Material</b>	Polyolefin

## Mechanical Specifications

<b>Pulling Tension, maximum</b>	11.34 kg   25 lb
---------------------------------	------------------

# 3071E-4/23

---

## Environmental Specifications

<b>Installation temperature</b>	0 °C to +60 °C (+32 °F to +140 °F)
<b>Operating Temperature</b>	-20 °C to +60 °C (-4 °F to +140 °F)
<b>Acid Gas Test Method</b>	IEC 60754-2
<b>Environmental Space</b>	Low Smoke Zero Halogen (LSZH)
<b>Flame Test Method</b>	IEC 60332-3-22
<b>Smoke Test Method</b>	IEC 61034-2

## Packaging and Weights

<b>Cable weight</b>	37.204 kg/km   25 lb/kft
---------------------	--------------------------

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



## SYSTIMAX 360™ GigaSPEED XL® 1100GS3 Evolve Category 6 U/UTP Distribution Module, 6 port

### Product Classification

#### Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

#### Portfolio

SYSTIMAX®

#### Product Type

Module

#### Product Brand

GigaSPEED XL®

### General Specifications

#### ANSI/TIA Category

6

#### Cable Type

Unshielded

#### Color

Cool gray

#### Conductor Type

Solid | Stranded

#### Intelligence Type

iPatch® ready

#### Modules, quantity

1

#### Rack Type

EIA 19 in

#### Rack Units

1

#### Termination Type

IDC

#### Total Ports, quantity

6

#### Wiring

T568A | T568B

### Dimensions

#### Height

43.688 mm | 1.72 in

#### Width

106.68 mm | 4.2 in

#### Depth

27.432 mm | 1.08 in

#### Compatible Diameter Over Dielectric, maximum

1.168 mm | 0.046 in

#### Compatible Diameter Over Dielectric, minimum

0.762 mm | 0.03 in

#### Compatible Conductor Gauge, solid

22 AWG | 24 AWG

# 760151167 | 360-IPR-1100-GS3-DM6

**Compatible Conductor Gauge, stranded**

22 AWG | 24 AWG

## Electrical Specifications

**Current Rating at Temperature**

1.5 A @ 20 °C | 1.5 A @ 68 °F

**Dielectric Withstand Voltage, RMS, conductive surface**

1,500 Vac @ 60 Hz

**Dielectric Withstand Voltage, RMS, contact-to-contact**

1,000 Vac @ 60 Hz

**Insulation Resistance, minimum**

500 MOhm

## Material Specifications

**Contact Plating Material**

Precious metals

**Material Type**

High-impact, flame retardant, thermoplastic | Powder-coated steel

**Termination Contact Plating**

Nickel

## Mechanical Specifications

**Plug Insertion Life, minimum**

750 times

**Plug Insertion Life, test plug**

IEC 60603-7 compliant plug

**Plug Retention Force, minimum**

133.447 N | 30 lbf

## Environmental Specifications

**Operating Temperature**

-10 °C to +60 °C (+14 °F to +140 °F)

**Storage Temperature**

-40 °C to +70 °C (-40 °F to +158 °F)

**Relative Humidity**

Up to 95%, non-condensing

**Flammability Rating**

UL 94 V-0

**Safety Standard**

UL | cUL

## Packaging and Weights

**Packaging quantity**

1

**Weight, net**

0.068 kg | 0.15 lb

## Regulatory Compliance/Certifications

**Agency**

**Classification**

CHINA-ROHS

Below maximum concentration value

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

REACH-SVHC

Compliant as per SVHC revision on [www.commscope.com/ProductCompliance](http://www.commscope.com/ProductCompliance)

ROHS Compliant

UK-ROHS Compliant

