


USX12-6W

Base Product



3.6m | 12ft Sentinel® Ultra High Performance, Super High XPD Antenna, dual-polarized, 5.925 – 7.125 GHz

Product Classification

Product Type

Microwave antenna

General Specifications

Antenna Type

USX - Sentinel® Ultra High Performance, Super High XPD Antenna, dual-polarized

Polarization

Dual

Side Struts, Included

2

Side Struts, Optional

3

Dimensions

Diameter, nominal

3.6 m | 12 ft

Electrical Specifications

Operating Frequency Band

5.925 – 7.125 GHz

Gain, Low Band

43.8 dBi

Gain, Mid Band

45 dBi

Gain, Top Band

45.8 dBi

Boresite Cross Polarization Discrimination (XPD)

40 dB

Front-to-Back Ratio

82 dB

Beamwidth, Horizontal

1 °

Beamwidth, Vertical

1 °

Return Loss

26 dB

VSWR

1.1

Radiation Pattern Envelope Reference (RPE)

7433

Electrical Compliance

ACMA FX03_6a, 6p7a | ETSI 302 217 Class 4 | IC 3059A | IC 3064A | US FCC Part 101A | US FCC Part 74A

USX12-6W

Cross Polarization Discrimination (XPD) Electrical Compliance

ETSI EN 302217 XPD Category 3

Electrical Specifications, Band 2

| | |
|---|-------------------|
| Operating Frequency Band | 5.725 – 5.850 GHz |
| Gain, Mid Band | 43.4 dBi |
| Beamwidth, Horizontal | 1.1 ° |
| Beamwidth, Vertical | 1.1 ° |
| Boresite Cross Polarization Discrimination (XPD) | 39 dB |
| Front-to-Back Ratio | 69 dB |


Mechanical Specifications

| | |
|--|------------------------|
| Compatible Mounting Pipe Diameter | 115 mm 4.5 in |
| Fine Azimuth Adjustment Range | ±5° |
| Fine Elevation Adjustment Range | ±5° |
| Wind Speed, operational | 201 km/h 124.896 mph |
| Wind Speed, survival | 200 km/h 124.274 mph |

USX12-6W

Antenna Dimensions and Mounting Information

HX / USX12



| Dimensions in inches (mm) | | | | | | |
|---------------------------|-----------|------------|--------------|-------------|-------------|------------|
| Antenna size, ft (m) | A | B | C | D | E | F |
| 12 (3.6) | 8.5 (216) | 28.2 (715) | 149.3 (3793) | 46.3 (1177) | 81.5 (2069) | 10.6 (269) |

Wind Forces at Wind Velocity Survival Rating

| | |
|---|---------------------------------|
| Axial Force (FA) | 26750 N 6,013.641 lbf |
| Angle α for MT Max | -120 ° |
| Side Force (FS) | 9450 N 2,124.445 lbf |
| Twisting Moment (MT) | -17550 N-m -155,330.594 in lb |
| Force on Inboard Strut Side | 13000 N 2,922.517 lbf |
| Force on Outboard Strut Side | 4500 N 1,011.64 lbf |
| Zcg without Ice | 708 mm 27.874 in |
| Zcg with 1/2 in (12 mm) Radial Ice | 854 mm 33.622 in |

USX12-6W

Weight with 1/2 in (12 mm) Radial Ice

656 kg | 1,446.231 lb

USX12-6W

Wind Forces at Wind Velocity Survival Rating Image



Packaging and Weights

Weight, net

361 kg | 795.868 lb

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

Classification

Designed, manufactured and/or distributed under this quality management system

* Footnotes

Operating Frequency Band

Bands correspond with CCIR recommendations or common allocations used throughout the world. Other ranges can be accommodated on special order.

USX12-6W

Gain, Mid Band

For a given frequency band, gain is primarily a function of antenna size. The gain of Andrew antennas is determined by either gain by comparison or by computer integration of the measured antenna patterns.

Boresite Cross Polarization Discrimination (XPD)

The difference between the peak of the co-polarized main beam and the maximum cross-polarized signal over an angle twice the 3 dB beamwidth of the co-polarized main beam.

Front-to-Back Ratio

Denotes highest radiation relative to the main beam, at $180^\circ \pm 40^\circ$, across the band. Production antennas do not exceed rated values by more than 2 dB unless stated otherwise.

Return Loss

The figure that indicates the proportion of radio waves incident upon the antenna that are rejected as a ratio of those that are accepted.

VSWR

Maximum; is the guaranteed Peak Voltage-Standing-Wave-Ratio within the operating band.

Radiation Pattern Envelope Reference (RPE)

Radiation patterns define an antenna's ability to discriminate against unwanted signals. Under still dry conditions, production antennas will not have any peak exceeding the current RPE by more than 3dB, maintaining an angular accuracy of $\pm 1^\circ$ throughout

Cross Polarization Discrimination (XPD) Electrical Compliance

The difference between the peak of the co-polarized main beam and the maximum cross-polarized signal over an angle twice the 3 dB beamwidth of the co-polarized main beam.

Wind Speed, operational

For VHLP(X), SHP(X), HX and USX antennas, the wind speed where the maximum antenna deflection is $0.3 \times$ the 3 dB beam width of the antenna. For other antennas, it is defined as a deflection is equal to or less than 0.1 degrees.

Wind Speed, survival

The maximum wind speed the antenna, including mounts and radomes, where applicable, will withstand without permanent deformation. Realignment may be required. This wind speed is applicable to antenna with the specified amount of radial ice.

Axial Force (FA)

Maximum forces exerted on a supporting structure as a result of wind from the most critical direction for this parameter. The individual maximums specified may not occur simultaneously. All forces are referenced to the mounting pipe.

Side Force (FS)

Maximum side force exerted on the mounting pipe as a result of wind from the most critical direction for this

parameter. The individual maximums specified may not occur simultaneously. All forces are referenced to the mounting pipe.

Maximum forces exerted on a supporting structure as a result of wind from the most critical direction for this parameter. The individual maximums specified may not occur simultaneously. All forces are referenced to the mounting pipe.

Twisting Moment (MT)