

HBXX-6513DS-VTM | HBXX-6513DS-A2M



4-port sector antenna, 4x 1710–2170 MHz, 65° HPBW, RET compatible

- Two DualPol® antennas under one radome
- Each antenna is independently capable of field adjustable electrical tilt
- Continuous wideband operation

This product will be discontinued on: December 30, 2025

General Specifications

Antenna Type	Sector
Band	Single band
Color	Light Gray (RAL 7035)
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	PVC, UV resistant
Radiator Material	Low loss circuit board
Reflector Material	Aluminum
RF Connector Interface	7-16 DIN Female
RF Connector Location	Bottom
RF Connector Quantity, high band	4
RF Connector Quantity, mid band	0
RF Connector Quantity, low band	0
RF Connector Quantity, total	4

Remote Electrical Tilt (RET) Information

Model with Factory Installed AISG 2.0 Actuator	HBXX-6513DS-A2M
---	-----------------

Dimensions

Width	305 mm 12.008 in
Depth	166 mm 6.535 in
Length	695 mm 27.362 in
Net Weight, without mounting kit	7.9 kg 17.416 lb

HBXX-6513DS-VTM | HBXX-6513DS-A2M

Array Layout



Array	Freq (MHz)	Conns
B1	1710-2170	1-2
B2	1710-2170	3-4

Left

Bottom

Right

(Sizes of colored boxes are not true depictions of array sizes)

Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	1710 – 2170 MHz
Polarization	±45°

Electrical Specifications

Frequency Band, MHz	1710–1880	1850–1990	1920–2170
Gain, dBi	14.5	14.6	14.9
Beamwidth, Horizontal, degrees	67.1	65.6	63.7
Beamwidth, Vertical, degrees	14.8	14	13.4
Beam Tilt, degrees	0–12	0–12	0–12
USLS (First Lobe), dB	15	15	15
Front-to-Back Ratio at 180°, dB	30	30	30
Front-to-Back Total Power at 180° ± 30°, dB	26	27	27
CPR at Boresight, dB	22	22	22
CPR at Sector, dB	7	8	8
Isolation, Cross Polarization, dB	30	30	30
VSWR Return loss, dB	1.4 15.6	1.4 15.6	1.4 15.6
PIM, 3rd Order, 2 x 20 W, dBc	-150	-150	-150

HBXX-6513DS-VTM | HBXX-6513DS-A2M

Input Power per Port, maximum, watts 350 350 350

Mechanical Specifications

Wind Loading @ Velocity, frontal 223.0 N @ 150 km/h (50.1 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral 53.0 N @ 150 km/h (11.9 lbf @ 150 km/h)
Wind Loading @ Velocity, rear 259.0 N @ 150 km/h (58.2 lbf @ 150 km/h)
Wind Speed, maximum 241 km/h (150 mph)

Packaging and Weights

Width, packed 485 mm | 19.094 in
Depth, packed 349 mm | 13.74 in
Length, packed 1253 mm | 49.331 in
Weight, gross 17.9 kg | 39.463 lb

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



Included Products

600899A-2 – Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance