EWSH-132



Universal Snap-in Hanger for elliptical waveguide 132

Product Classification	
Product Type	Hanger kit
General Specifications	
Cable Type	Elliptical waveguide
Cables per Hanger	1
Color	Silver
Hanger Type	Snap-in hanger
Mounting	3/4 in through hole
Dimensions	
Height	40.9 mm 1.61 in
Width	42.9 mm 1.689 in
Length	72.9 mm 2.87 in
Compatible Diameter, maximum	31 mm 1.22 in
Compatible Diameter, minimum	23.1 mm 0.909 in
Waveguide Size	WR62 WG18 R140
Electrical Specifications	
Return Loss Effect, maximum	0.1 dB
DTF Effect, maximum	0.1 dB
Material Specifications	
Material Type	Stainless steel
Machanical Cancifications	

Mechanical Specifications

Page 1 of 2

©2022 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: September 8, 2022



EWSH-132

Vibration Survival

≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)	
Corrosion Resistance, minimum with no degredation	≥500 hours in salt spray chamber	
Environmental Strength Capability	Double cable weight	
Packaging and Weights		
Height, packed	20 cm 7.874 in	
Width, packed	20 cm 7.874 in	
Length, packed	20 cm 7.874 in	
Packaging quantity	10	
Weight, gross	1.6 kg 3.527 lb	

Regulatory Compliance/Certifications

Agency

Classification

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system



Page 2 of 2

©2022 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: September 8, 2022

