


# 760253593 | MFC-STF-UNV-6X



Qwik II Connector™, ST, OM1, 0.25/0.9/2.0/3.0 mm, Beige, Single Pack

## Product Classification

<b>Regional Availability</b>	Asia   Australia/New Zealand   EMEA   Latin America   North America
<b>Portfolio</b>	CommScope®
<b>Product Type</b>	Fiber connector
<b>Product Brand</b>	OptiSPEED®   Qwik
<b>Product Series</b>	Qwik II

## General Specifications

<b>Body Style</b>	BTW
<b>Color</b>	Beige
<b>Color, boot</b>	Black
<b>Ferrule Geometry</b>	Factory polished
<b>Interface</b>	ST/UPC
<b>Interface Feature</b>	Field Installable   Mechanical splice

## Dimensions

<b>Length</b>	50.2 mm   1.976 in
<b>Compatible Cable Diameter, maximum</b>	0.9 mm   0.035 in
<b>Compatible Cable Diameter, minimum</b>	0.25 mm   0.01 in

## Material Specifications

<b>Ferrule Material</b>	Zirconia
-------------------------	----------

## Mechanical Specifications

<b>Cable Retention Strength, maximum</b>	1.00 lb @ 0°
--	--------------

## Optical Specifications

<b>Fiber Mode</b>	Multimode
-------------------	-----------

# 760253593 | MFC-STF-UNV-6X

---

<b>Fiber Type</b>	OM1
<b>Insertion Loss Change, mating</b>	0.3 dB
<b>Optical Components Standard</b>	ANSI/TIA-568. 3-D
<b>Insertion Loss Change, temperature</b>	0.3 dB
<b>Insertion Loss, maximum</b>	0.5 dB
<b>Insertion Loss, typical</b>	0.1 dB
<b>Return Loss, minimum</b>	20 dB

## Environmental Specifications

**Operating Temperature** -40 °C to +75 °C (-40 °F to +167 °F)

## Packaging and Weights

**Packaging quantity** 1

## \* Footnotes

**Insertion Loss Change, mating** TIA-568: Maximum insertion loss change after 500 matings

**Insertion Loss Change, temperature** Maximum insertion loss change from -10 °C to +60 °C (+14 °F to +140 °F)