SFG23HDX-12-B



G23HDX High Capacity Sector Frame, $12.5 \, \text{ft} \times 2.88 \, \text{in} \, \text{OD} \, \text{face pipes}$, Base Kit Only. No antenna pipes.

Product Classification

Product Type High capacity Tower sector frame

Product Series G2

General Specifications

Mounting Angle 60°, 203.2 mm (8 in) | Straight or tapered legs up to 203.2 mm (8 in) OD

Patent Number Patent pending

Pipe, quantity 0
Sectors, quantity 1

Tower Taper Non-tapered | Tapered

Dimensions

Face Width3.81 m | 12.5 ftWidth3,810 mm | 150 inFace Support Pipe Diameter73.025 mm | 2.875 inMounting Diameter, maximum218.44 mm | 8.6 inMounting Diameter, minimum38.1 mm | 1.5 inStand-off Distance1,066.8 mm | 42 in

Material Specifications

Material Type Hot dip galvanized steel

Mechanical Specifications

Wind Rating For Specifications, please contact steelproducts@commscope.com or call 800-255-1479

Wind Rating Test Method TIA/EIA-222-G



SFG23HDX-12-B

Packaging and Weights

Included Frame | Pipe mounts | Stiff arms (2) | Tower attachment

Packaging quantity 1

* Footnotes

Wind Rating BWS—Base Wind Speed; FBC—Florida Building Code

