## PPLARGDLCMPD



Propel ULL Singlemode Cabled Module, 1x12 duplex LC Propel module on End A to 1x12f MPO/UPC non-pinned on End B, 12 fiber LSZH Patchcord, Method A

- This component requires 3 of the 12 lanes on the Propel Panel blade
- Ultra-low loss (ULL) with Method A polarity
- End A module can be installed from rear of panel
- Serialized QR code provides easy access to factory optical test results

#### Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Portfolio SYSTIMAX®

**Product Type** Fiber cabled module

Product Brand Propel
Product Series PPL

Ordering Note Modules with patch cord cable are single subunit, and have no additional outer jacket

General Specifications

**Configuration Type** PROPEL Module to MPO Connector

Cable Color Yellow

**Cable Type** Patch cord LSZH

Interface, front LC/UPC

Interface Feature, front Duplex | Shuttered

Interface Color, front Blue

Interface, rear MPO-12/UPC Female

Interface Feature, rear Key up/down | Unpinned

Module Size, end A8 fiberModule Size, end B8 fiberModule Quantity, end A1

Module Quantity, end B

**Polarity** Method A

Total Fibers, quantity 12

Total Ports, quantity, front 6

**COMMSCOPE®** 

# PPLARGDLCMPD

#### **Dimensions**

 Height
 11 mm | 0.433 in

 Width
 65 mm | 2.559 in

 Depth
 170 mm | 6.693 in

**Breakout Length, end B** 12 in | 120 in | 33 in | 36 in | 48 in | 60 in | 72 in

Cable Assembly Length Range (m)1-400Cable Assembly Length Range (ft)2-999

## Ordering Tree



#### **Optical Specifications**

Fiber Mode Singlemode

Fiber Type OS2
Insertion Loss, maximum 0.6 dB

## **Environmental Specifications**

**Qualification Standards** IEC 61753-1 | TIA-568.3-D

Safety Standard c-UL-us

Packaging and Weights

Packaging quantity 1

**COMMSCOPE®** 

# **PPLARGDLCMPD**

## Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Above maximum concentration value

ROHS Compliant/Exempted UK-ROHS Compliant/Exempted



#### Included Products

760245203 – N-012-MP-8G1-F20YL/E Low Smoke Zero Halogen Riser Light Duty Interconnect Cable, 12 fiber

